

Specializing in transportation adhesives and sealant, **Pegus Systems** works closely with its clients to offer the best solution that will not only meet their adhesive needs, but also add value to their operation. We do this by providing reliable products, complementary accessories, professional logistical services and personalized client services.

Pegus Systems strives to create relationships of support and collaboration with our distributors. Our success is dependent on our distributor's success. We do all we can to ensure that our adhesives and sealant add value to their commercial strategy. Unlike our larger competitors, we're 100% focused on the automotive aftermarket replacement of windshields and auto-body sealing. We devote all our resources to this industry.



P330 is a one component industrial grade polyurethane sealant, which has a variety of applications for the automotive and transportation industry.



P330 Characteristics

- ▶ Available in black, gray, beige and white
- ▶ Available in 310ml cartridges and also in 600ml foil packs
- ▶ Packaged 25 cartridges per case or 12 foil packs per case
- ▶ For technical characteristics see our Technical Data Sheet located at www.pegus.us



Application Recommendations

- ▶ Bonding and sealing different materials used in the transportation and general industry, including lacquered metals, glass, aluminum, wood, etc.
- ▶ Sealing seams between parts in transportation and marine industries
- ▶ Bonding for many glass-related applications in the transportation industry (consult your Pegus distributor)



Shelf Life

- ▶ P330 offers a twelve-month shelf life. Maximum shelf life is achieved only when the product is stored in an ambient temperature that does not exceed 23°C and 50% relative humidity
- ▶ For maximum shelf life, avoid direct exposure to the sun for extended periods of time
- ▶ Proper handling is required to avoid damage to the packaging which may cause moisture penetration and reduced shelf life



Safety Procedures

- ▶ Avoid contact with skin and eyes. If eye contact occurs, flush out with water for 15 minutes and seek medical attention.
- ▶ Use in properly ventilated areas.
- ▶ Handle with proper safety equipment such as gloves and protective eyewear.
- ▶ Refer to the Material Safety Data Sheet for additional information.



Pegus Promise

- ▶ Pegus Systems guarantees respectful collaboration with our distributors.
- ▶ Pegus Systems understands the importance of having reliable material and will provide product expiration information before shipping.
- ▶ Pegus Systems will use its extensive experience and knowledge of logistics to facilitate the most competitive delivery of our products to any port around the world.




Accessories



PEGUS SYSTEMS COMBO PRIMER

Combo primer for maximum adhesion. Protects against rust and offers a better UV resistance.



WOOL DAUBER APPLICATORS

Variety of applicators available for convenient application of primer.



AP200 REAR VIEW MIRROR ADHESIVE

Two component non spray rear view mirror adhesive. Over 200 applications in one kit. Excellent UV resistance.



MODEL 250 HIGH EXTRUSION APPLICATOR

18:1 extrusion ratio. Excellent for high viscosity extrusion.



HAP203 CUT-OUT WIRE

Braided strands for fast cutting. 21.9m per coil. Complete kits also available.